

FS-M9

FRESATRICE COPIATRICE
MANUAL COPY ROUTER MACHINE






1. L'intestatrice **FS-M9** è dotata di un dispositivo per le lavorazioni fuori squadra e con gradazioni fisse che vanno da $-45^\circ / 90^\circ / +45^\circ$ con relative gradazioni intermedie.
2. Fermo rotativo con 6 posizioni per la regolazione della profondità di fresatura.
3. Possibilità di effettuare lavorazioni in fuori squadra tramite fermo meccanico.
4. Carter integrale per la zona di lavoro.



1. The **FS-M9** end milling machine is equipped with a device for working with fixed gradations ranging from $-45^\circ / 90^\circ / +45^\circ$ with relative intermediate gradations.
2. Turret stop with 6 positions for adjusting the milling depth.
3. Possibility of milling operations on intermediate degrees by mechanical stop.
4. Integral carter for the work area.

MISURE E CARATTERISTICHE TECNICHE MEASUREMENTS AND TECHNICAL CHARACTERISTICS

 <p>A=mm 370 B=mm 1200 C=mm 900</p>	 <p>kg Kg 110</p>	 <p>A=mm 150 max B=mm 80 max</p>
 <p>380 V 50 Hz</p>	 <p>1.5 kW 4 Poli</p>	 <p>D=mm 140 max mm 50 min DA=mm 27</p>
 <p>2800 n/min</p>	 <p>7 bar 5 L/ciclo</p>	 <p>n. 1 1.5 kW</p>

